



MP-839 IZOPRIME



PACKAGING

9 L



MIXING RATIO

5/1-4/1



CONSUMPTION

0.25-0.3L/m²

Description

MP-839 IZOPRIME is a black, cold bitumen emulsion in water. It is not flammable and creates a waterproofing layer after it dries. Provides a perfect adhesion to all construction materials. It has an easy and efficient application.

Application

MP-839 IZOPRIME is used to waterproof vertical or horizontal surfaces, for regeneration of old, bituminous coatings and as a vapor barrier. It can also be used as a primer on which the bituminous membrane is placed. Apply with brush, roller or spray gun. Reinforce with fiberglass between two layers. It can be diluted with clean water with a 30% proportion. More than two layers are recommended for the best results. If used as a primer it is diluted by up to 50% and the consumption is 0.3m²/L. The second layer should not be applied before the first one has thoroughly dried. Tools are cleaned in water before emulsion is dried. It is not recommended to apply the primer to surfaces with high humidity conditions and temperatures of less than 5°C or higher than 25°C.

Consumption

It consumes 0.25-0.3L/m² depending on the surface.

TECHNICAL DATA (IN +23°C AND 50% RH.)

Form	Liquid
Colour	Black
Storage	24 months when stored in the original sealed packaging in a dry place.
Mixing Ratio	5/1 - 4/1
Application Temperature	(+5°C) - (+35°C)
Drying Time	1 hour
Density	1g/cm ³
Solid Material Ratio	48%
Ready to Use	5-6 Hours