



MP - 819 BETOPRIME



PACKAGING

3L / 9L



CONSUMPTION

0.25kg/m²

Description

MP-819 BETOPRIME is an acrylic primer with a “micronized resin” base and supplemented with quartz, used for coating surfaces before painting them. It can be used for concrete, cement, plaster, gypsum, etc. It stabilizes the surface and decreases the porosity of the surface, thus reducing the final material consumption and avoiding cracking or falling of it. It also protects the surface from humidity by isolating it. MP-819 BETOPRIME dries quickly and creates the perfect surface for the final coating.

Application

The surface that will be painted with MP-819 BETOPRIME must be dry (free from moisture) and free of dust, solid debris or oils. It is recommended that the damaged parts must be repaired before application. MP-819 BETOPRIME can be applied with a brush or roller.

Consumption

It consumes 0.25kg/m² depending on the surface.

Drying time

It dries in 24 hours, depending on the climatic conditions.

Warning

It is not recommended to apply a primer to surfaces with high humidity conditions of the environment and temperatures of less than 5°C and higher than 25°C. After the application, the equipment should be washed immediately with soap and water.

TECHNICAL DATA (IN +23°C AND 50% U.R.)

| | |
|-------------------------|--|
| Form | Liquid |
| Colour | Dark Pink |
| Storage | 12 months when stored in the original sealed packaging in a dry place. |
| Application Temperature | (+5°C) - (+35°C) |
| Drying Time | 24 Hours |