



MP - 849 LISOPRIME



PACKAGING

3L / 9L

Description

MP-849 LISOPRIME SMOOTH SURFACE PRIMER is a solvent - free, polymer dispersion based, pigmented primer suitable for new ceramic tile over existing tile.

Fields of Application

-Smooth and dense surfaces such as tile, sand-stone, marble, clinker, plywood and also absorbent surfaces such as gypsum, plaster, concrete, screed, wood.

Properties

-Increases the adhesion strength of tile adhesives on smooth and glossy surfaces by forming a rough surface.
-Reinforces the substrate and thus increases the adhesion of tile adhesive on unsound surfaces.
-Ready to use. Easily applicable with either roller or brush.
-Solvent free. Does not smell and does not harm the environment.

Preparation of Substrates

-Surfaces must be cured.
-Surface should be cleaned from dust, dirt, oil and old blistered coatings that may prevent good adhesion.
-The sub-surfaces that are not strong enough to carry themselves e.g., cracked plasters, weak surfaces, or residues of moss should be cleaned from the application surface.
-If necessary, surface cracks should be filled, and substrate should be evened with MATIART series.

Application

-Stir MP-849 LISOPRIME SMOOTH SURFACE PRIMER before the application and apply with a brush or roller.
-Apply two coats absorbent substrates like gypsum, plaster, screed and concrete.

Post-Application Protection & Suggestions

-Drying time is 45 - 60 minutes. Do not apply anything within this period.
-Surface temperature must be min. 5°C and there must not be precipitation.
-Hands and equipment used should be washed well.
-It is not suitable for wet-duty areas or areas which are permanently submerged.

TECHNICAL DATA (IN +23°C AND 50% U.R.)

Form	Liquid
Colour	Light Blue
Storage	12 months when stored in the original sealed packaging in a dry place.
Application Temperature	(+5°C) - (+35°C)
Density	1.17 g/cm ³
Drying Time	48 Hours