

## MF-200 MATISTUCCO

Ultra fine-grained, polymer-modified, cement-based powder filler.



### PACKAGING

15kg



### MIXING RATIO

4-5 L/25kg



### CONSUMPTION

1-2 kg/m<sup>2</sup>

### Description

MF-200 MATISTUCCO is an ultra-fine-grained, white, cement-based powder filler enhanced with polymers. MF-200 MATISTUCCO creates a smooth surface without vertical slip. It is resistant and it can be used for indoor and outdoor surfaces.

### Area of Use

- It is used to smooth walls and ceilings filled with mortar or prepared lime and cement-based mortar.
- It is used to smooth concrete surfaces.
- It is used to smooth gypsum-board walls and ceiling.

### Substrate Preparation

The surface must be free of dust, paint, loose material, etc. Priming or preparation with oil is not required prior to application to plaster or concrete. Plasterboards must be primed with MP-859 UNIPRIME.

### Application

- Mix MF-200 MATISTUCCO with clean water slowly to obtain a homogeneous paste, free from lumps.
- The material is applied with a spatula in two layers.
- The second layer can be applied after the first one has dried (after 2-3 hours).

-Sanding and painting of the surface can follow after 12 hours.

### Consumption

It consumes 1-2kg/m<sup>2</sup> depending on the surface

### Features



## Technical Data (IN +23 °C AND 50% U.R.)

Form	Powder
Color	White
Capillary Water Absorption (EN1015-18)	W0
Water Vapour Permeability (EN1015 -19)	$\mu$ :21
Adhesion (EN1015-12)	$\geq 0,5 \text{ N/mm}^2$
Thermal conductivity $\lambda_{10 \text{ dry}}$ (EN1745)	0,24 W/mK
Reaction to Fire	A1
Release of Dangerous Substances	See SDS

### MATIS Construction Chemicals

Tiranë, Albania

info@matis-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.matis-eu.com](http://www.matis-eu.com), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.