

MF-250 MATIFIN 10 STANDARD

Fine-grained, polymer-modified, cement-based powder filler.



PACKAGING

25kg



MIXING RATIO

5.5-6 L/25kg



CONSUMPTION

2 kg/m²

Description

MF-250 MATIFIN 10 STANDARD is a polymer-modified, cement-based, fine-grained powder filler, for indoor or outdoor applications.

Area of Use

- It is used to smooth and repair exposed concrete.
- It is used to fill cracks, pores or cavities in concrete surfaces.
- It is used for full-surface smoothing with very thin layers.

Substrate Preparation

The surface must be free of dust, paint, loose material, etc.

Application

25 kg MF-250 MATIFIN 10 STANDARD must be slowly poured onto 5,5 – 6L water and mixed until a homogeneous mixture is obtained. Mixing must be done with low-speed mixer. Any additives not specified in the application instructions must not be added.

MF-250 MATIFIN 10 STANDARD must be applied with a steel trowel not to exceed 10 mm in one coat. For applications with thicknesses more than 10 mm, application must be made after at least 1 day.

Consumption

It consumes 2kg/m² depending on the surface

Features



Technical Data (IN +23 °C AND 50% U.R.)

Form	Powder
Color	White / Grey
Compressive Strength (EN12190)	Class R2
Adhesive Bond (EN1542)	≥ 0,75 MPa
Thermal compatibility (EN 13687-1)	≥ 0,75 MPa
Capillary Absorption (EN13057)	≤ 0,5 kg/m ² .h ^{0,5}
Reaction to Fire	A1
Release of Dangerous Substances	See SDS

MATIS Construction Chemicals

Tiranë, Albania

info@matis-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.