

MM-420 MATIMOR

Cement-based mortar for masonry construction.



PACKAGING

25kg



MIXING RATIO

5-6 L/25kg



CONSUMPTION

20-25 kg/m²

Description

MM-420 MATIMOR is a cement-based mortar for masonry construction for indoor or outdoor applications.

Area of Use

-It is used for various types of building materials such as bricks, blocks, aerated concrete blocks, stone, etc.

Application

MM-420 MATIMOR is slowly added to water under continuous stirring, until a homogeneous paste is formed. A low-speed mixer is recommended for mixing. MM-420 MATIMOR can be applied using a trowel.

Consumption

It consumes 20-25kg/m² depending on the brick dimensions.

Features



Technical Data (IN +23 °C AND 50% U.R.)

Form	Powder
Color	Grey
Storage	24 months when stored in the original sealed packaging in a dry place.
Mixing Ratio	5-6 L/25kg
Application Temperature	(+5°C) - (+35°C)
Maximal thickness for one layer	25 mm
Working time	3-4 hours
Reaction to fire	A1
Dangerous Substances	See SDS

MATIS Construction Chemicals

Tiranë, Albania

info@matis-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.