

MP-819 BETOPRIME

High adhesion, water based primer for smooth or non-porous substrates



PACKAGING

5kg/20kg



CONSUMPTION

0.25kg/m²

Description

MP-819 BETOPRIME is an adhesion primer with synthetic resins and quartz sand.

Area of Use

-It is used on smooth or non-absorbent surfaces to increase the adhesion of the plaster or render layer.

Substrate Preparation

The surface to be primed must be dry and free of dust, grease, dirt, etc.

Application

-MP-819 BETOPRIME is stirred and applied over the substrate by brush or roller.

Consumption

It consumes 0.25kg/m² depending on the surface.

Features



Technical Data (IN +23 °C AND 50% U.R.)

Form	Paste
Color	Dark Red
Release of Dangerous Substances	See SDS

MATIS Construction Chemicals

Tiranë, Albania

info@matis-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.