

MP-859 UNIPRIME

High penetrating, multi-purpose acrylic water based primer.



PACKAGING

5kg



CONSUMPTION

100-200g/m²

Description

MP-859 UNIPRIME is a polymer emulsion with high penetrating ability used to consolidate porous substrates, ensuring proper adhesion of water based paints, tile adhesives, screeds, flexible mortars and liquid-applied elastomeric membranes.

Area of Use

- Preparation of concrete screeds or slabs.
- Preparation of wood surfaces, wood panels (CTB-H, CTB-X), old tiles or natural stone.
- Preparation of thermoplastic slabs
- Preparation of surfaces on which traces of glue or old, well-adhering levelling compounds remain.

Substrate Preparation

The surface to be primed must be dry and free of dust, grease, dirt, etc.

Application

-MP-859 UNIPRIME is stirred and applied over the substrate by brush, roller, or spray.

Consumption

It consumes 100-200g/m² depending on the surface.

Features



Technical Data (IN +23 °C AND 50% U.R.)

Form	Liquid
Color	White
Release of Dangerous Substances	See SDS

MATIS Construction Chemicals

Tiranë, Albania

info@matis-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.