

MP-860 MATIGRIP ECO

Multi-purpose, high adhesion, water based quartz primer for smooth or non-porous substrates.





Description

MP-860 MATIGRIP ECO is multi-purpose, high adhesion, water based quartz primer for smooth or non-porous substrates.

Area of Use

- -Improving the bond of adhesives for smoothing ceramics and levelling compounds on non-absorbent surfaces.
- -Improving the bond of cement and lime-based plasters on substrates made from concrete, brickwork, compressed concrete blocks.
- -Laying ceramic and natural stone floors directly on top of old ceramic floors.
- -Adhesion promoter for cementitious smoothing compounds on substrates previously consolidated or waterproofed.
- -Application of render on concrete, brickwork, etc.

Substrate Preparation

The surface to be primed must be dry and free of dust, grease, dirt, etc.

Application

MP-859 UNIPRIME is stirred and applied over the substrate by brush, roller, or spray.

If after the application of the first layer the surface has not been completely covered with the material, then a second layer should be applied, after the first one has dried.

Consumption

It consumes 100-200g/m2 depending on the surface.

Features













Technical Data (IN +23°C AND 50% U.R.)

Form	Liquid
Color	Grey
Release of Dangerous Substances	See SDS

MATIS Construction Chemicals

Tiranë, Albania info@matis-eu.com www.matis-eu.com T: +355 69 20 94 570