

## MR-810 MATIART

Polymer-modified, cementitious repair mortar.



### PACKAGING

25kg



### MIXING RATIO

4-5 L/25kg



### CONSUMPTION

15 kg/m<sup>2</sup>

### Description

MR-810 MATIART 10 is a polymer-modified, cement-based, repair mortar without corrosive ingredients, suitable for indoor and outdoor.

### Area of Use

- It is used for concrete or brickwork repair and patching.
- It is used for forming fillets at wall to floor junctions.
- It is used for fixing ridge tiles on roofs.

### Substrate Preparation

The surface must be free of dust, paint, loose material, etc.

### Application

MR-810 MATIART 10 is added to water under continuous stirring, until a mixture of the desired workability is formed. The material is applied with a trowel.

### Consumption

It consumes 15kg/m<sup>2</sup>/cm depending on the surface.

### Features



## Technical Data (IN +23 °C AND 50% U.R.)

Form	Powder
Color	White / Grey
Compressive Strength (EN12190)	Class R2
Adhesive Bond (EN1542)	≥ 0,82 MPa
Thermal compatibility (EN 13687-1)	≥ 0,82 MPa
Capillary Absorption (EN13057)	≤ 0,5 kg/m <sup>2</sup> .h <sup>0,5</sup>
Reaction to Fire	A1
Release of Dangerous Substances	See SDS

### MATIS Construction Chemicals

Tiranë, Albania

info@matís-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.matis-eu.com](http://www.matis-eu.com), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.