

## GS-11 GRAFIATO STRUCTURE

Premium, akrilna, spremna za upotrebu, izuzetno vodoodbojna fasadna malter.



### PAKOVANJE

25kg



### POTROŠNJA

1mm - 2kg/m<sup>2</sup> | 1.5mm - 3kg/m<sup>2</sup> | 2mm - 3.6kg/m<sup>2</sup>

### Opis

GS-11 GRAFIATO STRUCTURE premium, akrilna, spremna za upotrebu, izuzetno vodoodbojna fasadna malter. Nudi visoku elastičnost i visoku adheziju na podlogu.

GS-11 GRAFIATO STRUCTURE ima odličnu paropropusnost, sprečava stvaranje pukotina i nema potrebe za farbanjem fasade nakon nanošenja.

### Oblast upotrebe

- Koristi se kao tanak završni sloj maltera za stvaranje bele ili obojene, vodoodbojne završne obrade.

- Koristi se kao dekorativna završna obrada u MATIS sistemima toplotne izolacije.

### Priprema podloge

Površina treba da bude očišćena od prašine, masnoće, slobodnih čestica, boja, itd. Preporučuje se da je navlažite pre nanošenja.

Koristite PG-551 PRIMER GRAFIATO da povećate prijanjanje GS-11 GRAFIATO STRUCTURE na površinu.

### Aplikacija

GS-11 GRAFIATO STRUCTURE treba dobro promešati pre nanošenja, sporim, kružnim pokretima kako bi se sprečilo zarobljavanje vazduha.

GS-11 GRAFIATO STRUCTURE se nanosi ručno, pomoću glatke, nerđajuće čelične gleterice ili mašinom za malterisanje.

Dok se još nije kompleksno osušio (5-15 min. nakon nanošenja), GS-11 GRAFIATO STRUCTURE se tretira (presuje) plastičnom gletericom.

### Potrošnja

U zavisnosti od površine troši 2kg/m<sup>2</sup> za 1mm, 3kg/m<sup>2</sup> za 1,5mm i 3,6kg/m<sup>2</sup> za 2mm.

### Karakteristike



## Tehnički podaci (IN +23 °C I 50% U.R.)

Forma	Zalepите
Boja	Bela
Skladištenje	24 meseca kada se čuva u originalnom zatvorenom pakovanju na suvom mestu.
Gustina (EN ISO 2811, DIN 53217, ASTM D 1475)	1.7-2.0 g/cm <sup>3</sup>
Viskoznost (RVDV -2T, R7)	15000-30000 cp
pH	≥8
Otpornost na vlagu	Osušite nakon 24 sata u normalnim uslovima
Temperatura primene	(+5°C) - (+35°C)
Sila smicanja (RVDV -2T, R7)	30,000-600,000 newton/m <sup>2</sup>
% (RVDV -2T, R7)	10-90%
Kinematička viskoznost (RVDV -2T, R7)	5000-10000 mm <sup>2</sup> /s

### MATIS Construction Chemicals

Tiranë, Albania

info@matís-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.matis-eu.com](http://www.matis-eu.com), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.