

MF-200 MATISTUCCO

Ultra finozrnasti, polimerno-modifikovani, cementni prah za popunjavanje.



PAKOVANJE
15kg



ODNOSI MEŠANJA
4-5 L/25kg



POTROŠNJA
1-2 kg/m²

Opis

MF-200 MATISTUCCO is an ultra-fine-grained, white, cement-based powder filler enhanced with polymers. MF-200 MATISTUCCO creates a smooth surface without vertical slip. It is resistant and it can be used for indoor and outdoor surfaces.

Područje primene

- Koristi se za zaglađivanje zidova i plafona popunjenih malterom ili pripremljenim malterima na bazi kreča i cementa.
- Koristi se za zaglađivanje betonskih površina.
- Koristi se za zaglađivanje zidova i plafona od gipsanih ploča.

Priprema podloge

Površina mora biti čista od prašine, boje, labavih materijala i slično. Nema potrebe za prajmerom ili pripremom sa uljem pre primene na malter ili beton. Zidne ploče od gipsa treba prekriti prajmerom MP-859 UNIPRIME.

Primena

- Pomešajte MF-200 MATISTUCCO sa čistom vodom polako dok ne dobijete homogenu pastu bez grudvica.
- Materijal se nanosi spatulom u dva sloja.
- Drugi sloj može se naneti nakon što se prvi osuši (posle 2-3 sata).

-Brušenje i farbanje površine može uslediti nakon 12 sati.

Potrošnja

Potrebna količina je 1-2 kg/m² u zavisnosti od površine.

Karakteristike



Tehnički podaci (IN +23 °C I 50% U.R.)

Forma	Puder
Boja	Bela
Kapilarna apsorpcija vode (EN1015-18)	W0
Propustljivost vodene pare (EN1015 -19)	μ :21
Adhezija (EN1015-12)	$\geq 0,5$ N/mm ²
Toplotna provodljivost $\lambda_{10 \text{ dry}}$ (EN1745)	0,24 W/mK
Reakcija na vatru	A1
Opuštanje opasnih supstanci	Vidi SDS

MATIS Construction Chemicals

Tiranë, Albania

info@matís-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.