

MF-270 MATIFIN 50 ANTIQUE

Grubožrnasti, polimerno-modifikovani, cementni prah za popunjavanje



PAKOVANJE
25kg



ODNOSI MEŠANJA
5.5-6 L/25kg



POTROŠNJA
2 kg/m²

Opis

MF-270 MATIFIN 50 ANTIQUE je polimerno-modifikovani, cementni, grubožrnasti prah za popunjavanje, za unutrašnje i spoljne primene sa grubom teksturom.

Područje primene

- Koristi se za zaglađivanje i popravku izloženog betona.
- Koristi se za popunjavanje pukotina, pora ili šupljina na betonskim površinama.
- Koristi se za potpuno zaglađivanje površina vrlo tankim slojevima.

Priprema podloge

Površina mora biti čista, bez prašine, boje, labavih materijala i slično.

Primena

25 kg MF-270 MATIFIN 50 ANTIQUE treba polako posuti u 5,5 – 6L vode i mešati dok se ne dobije homogena mešavina. Mešanje treba obaviti sa mikserom niske brzine. Ne smete dodavati nikakve aditive koji nisu navedeni u uputstvu za primenu. MF-270 MATIFIN 50 ANTIQUE treba naneti čeličnom gladilicom, ne prelazeći 10 mm u jednom sloju. Za deblje slojeve od 10 mm, primena treba da se obavi nakon najmanje 1 dan.

Potrošnja

Potrebna količina je 2 kg/m² u zavisnosti od površine.

Karakteristike



Tehnički podaci (IN +23° C I 50% U.R.)

Forma	Puder
Boja	Bela/Grei
Čvrstoca na pritisak (EN12190)	Class R2
Adhezivna veza (EN1542)	≥ 0,75 MPa
Termička kompatibilnost (EN 13687-1)	≥ 0,75 MPa
Kapilarna apsorpcija (EN13057)	≤ 0,5 kg/m ² .h ^{0,5}
Reakcija na vatru	A1
Oslobađanje opasnih supstanci	Vidi SDS

MATIS Construction Chemicals

Tiranë, Albania

info@matís-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.