

MI-839 IZOPRIME

Vodonosna, bitumenska vodonepropusna emulzija.



PAKOVANJE

9L



POTROŠNJA

1.5-2.5 kg/m²

Opis

MI-839 IZOPRIME je vodonosna, bitumenska vodonepropusna emulzija.

Područje primene

- Koristi se za vodonepropusnu zaštitu betonskih površina, kao što su ravni krovovi, temelji, spoljašnji zidovi, podovi.
- Koristi se kao osnovni premaz pre postavljanja bitumenskih vodonepropusnih membrana i za održavanje postojećih bitumenskih slojeva.

Priprema podloge

Površina koja će biti prekrivena treba da bude čista, bez prašine, masti, labavih čestica, boja itd.

Primena

MI-839 IZOPRIME treba dobro promešati pre primene. Nanosi se četkom ili valjkom. MI-839 IZOPRIME se nanosi kao osnovni premaz tako što se prvi sloj razblaži sa 50% vode, a nakon što se prvi sloj osuši, nanose se još dva sloja koja se razblaže sa 25% vode.

Potrošnja

Potrošnja MI-839 IZOPRIME-a je 1.5-2.5 kg/m², u zavisnosti od površine.

Karakteristike



Tehnički podaci (IN +23°C I 50% U.R.)

Forma	Tečnost
Boja	Crno
Skladištenje	24 meseca kada se čuva u originalnom zatvorenom pakovanju na suvom mestu.
Potrošnja	1.5-2.5k/m ²
Temperatura primene	(+5°C) - (+35°C)
Gustina	1g/cm ³
Odnos čvrstog materijala	48%

MATIS Construction Chemicals

Tiranë, Albania

info@matís-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.