

MP-819 BETOPRIME

Visoka adhezija, akrilni primer na bazi vode za glatke ili neporozne podloge



PAKOVANJE

5kg/20kg



POTROŠNJA

0.25kg/m²

Opis

MP-819 BETOPRIME je primer za adheziju sa sintetičkim smolama i kvarcnim peskom.

Područje primene

Koristi se na glatkim ili neupijajućim površinama za povećanje adhezije malterskog ili premaza sloja.

Priprema podloge

Površina koja se premazuje mora biti suva i očišćena od prašine, masti, prljavštine i sl.

Primena

MP-819 BETOPRIME treba dobro promešati i naneti na podlogu četkom ili valjkom.

Potrošnja

Potrebna količina je 0,25 kg/m² u zavisnosti od površine.

Karakteristike



Tehnički podaci (IN +23° C I 50% U.R.)

Forma	Zalepíte
Boja	Tamno crvena
Oslobađanje opasnih supstanci	Vidi SDS

MATIS Construction Chemicals

Tiranë, Albania

info@matís-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.