

MT-730 GRATECH

Polimerno modifikovani, vodoodbojni, cementni malter.



PAKOVANJE
25kg



ODNOSI MEŠANJA
5.75-6.5 L/25kg



POTROŠNJA
2.4-2.8 kg/m²

Opis

MT-730 GRATECH je polimerno modifikovan, vodoodbojni, cementni malter.

Područje primene

- Koristi se za kreiranje dekorativne završnice na podlogama gde su potrebni visoka fleksibilnost i adhezija.
- Koristi se kao dekorativna završnica u MATIS termoizolacionim sistemima.

Priprema podloge

Površina treba biti čista od prašine, masti, labavih čestica, boja itd. Preporučuje se blago vlaženje površine pre nanošenja.

Koristite PG-551 PRIMER GRAFIATO za poboljšanje adhezije MT-730 GRATECH na podlogu.

Primena

MT-730 GRATECH se polako dodaje u vodu uz kontinuirano mešanje, dok se ne formira homogena pasta. Preporučuje se korišćenje miksera sa niskim brojem obrtaja.

Nanosi se ručno, koristeći gleter ili mašinu za malterisanje. Nakon što se dovoljno osuši, ručno se izgladuje pomoću sunđera.

Potrošnja

Potrošnja iznosi 2.4-2.8 kg/m², u zavisnosti od površine.



Tehnički podaci (IN +23 °C I 50% U.R.)

Forma	Puder
Boja	Bela
Skladištenje	12 meseca kada se čuva u originalnom zatvorenom pakovanju na suvom mestu.
Odnos mešanja	5.75-6.5 L / 25 kg
Potrošnja	2.4-2.8 kg/m ²
Temperatura primene	(+5°C) - (+35°C)
Gustina mešavine očvrslog maltera	1400 ± 100 kg/m ³
Snaga vezivanja (EN 1015-12)	≥ 0.45 N/mm ² /B
Čvrstoca na pritisak/ klasa (EN 1015-11)	3.5-7.5 N/mm ² -CS III
Kapilarna apsorpcija vode (EN ISO 1062-3)	< 0.1 kg/m ² h ^{0.5}
Reakcija na vatru	Bs1d0
Opasne supstance	Vidi SDS

MATIS Construction Chemicals

Tiranë, Albania

info@matis-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.