

PG-551 PRIMER GRAFIATO

Vodo-bazni, beli, akrilni primer za fasadne maltere sa kvarcnim peskom.



PAKOVANJE

5kg/20kg



POTROŠNJA

0.25kg/m²

Opis

PG-551 PRIMER GRAFIATO je vodo-bazni, beli, akrilni premaz za fasadne maltere sa kvarcnim peskom.

PG-551 PRIMER GRAFIATO obezbeđuje ravnomerno obojenu završnu površinu, posebno kada je izabran tamniji fasadni malter.

Područje primene

-Koristi se kao gotov premaz pre nanošenja dekorativnog maltera.

Priprema podloge

Površina treba biti čista od prašine, masti, labavih čestica, boja itd. Preporučuje se blago vlaženje površine pre nanošenja.

Primena

PG-551 PRIMER GRAFIATO treba dobro promešati pre nanošenja, laganim kružnim pokretima kako bi se izbeglo zadržavanje vazduha.

Nanosu se četkom ili valjkom.

Potrošnja

Potrošnja iznosi 0.25 kg/m², u zavisnosti od površine.

Karakteristike



Tehnički podaci (IN +23 °C I 50% U.R.)

| | |
|---|---|
| Forma | Tečnost |
| Boja | Bela |
| Skladištenje | 24 meseca kada se čuva u originalnom zatvorenom pakovanju na suvom mestu. |
| Gustina (EN ISO 2811, DIN 53217, ASTM D 1475) | 1.65-1.75 g/cm ³ |
| Viskoznost (RVDV -2T, R7) | 5500-6500 cp |
| pH | ≥8 |
| Otpornost na vlagu | Osušite nakon 24 sata u normalnim uslovima |
| Temperatura primene | (+5°C) - (+35°C) |
| Sila smicanja (RVDV -2T, R7) | 10000-15000 newton/m ² |
| % (RVDV -2T, R7) | 10-70% |
| Kinematička viskoznost (RVDV -2T, R7) | 2000-5000 mm ² /s |

MATIS Construction Chemicals

Tiranë, Albania

info@matis-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.