

MM-420 MATIMOR

Malta a base di cemento per la costruzione di murature.



IMBALLAGGIO
25kg



RAPPORTO DI MISCELAZIONE
5-6 L/25kg



CONSUMO
20-25 kg/m²

Descrizione

MM-420 MATIMOR è una malta a base di cemento per la costruzione di murature, adatta per applicazioni interne ed esterne.

Campo di Applicazione

-Viene utilizzata per vari tipi di materiali da costruzione come mattoni, blocchi, blocchi in calcestruzzo cellulare, pietra, ecc.

Applicazione

MM-420 MATIMOR deve essere aggiunto lentamente all'acqua sotto agitazione continua, fino a formare una pasta omogenea. Si consiglia l'uso di un miscelatore a bassa velocità per la miscelazione.

MM-420 MATIMOR può essere applicato con una spatola.

Consumo

Il consumo è di 20-25 kg/m², a seconda delle dimensioni dei mattoni.

Caratteristiche



Scheda Tecnica (A +23° C E 50% U.R.)

Forme	Polvere
Colore	Grigio
Magazzinaggio	12 mesi se conservato nell'originale confezione sigillata in un luogo asciutto.
Rapporto di miscelazione	5-6 litri di acqua / 25 kg
Temperatura di Applicazione	(+5°C) - (+35°C)
Spessore massimo per mano	25 mm
Tempo di miscelazione	3-4 ore
Reazione al fuoco	A1
Sostanze pericolose	Vedi SDS

MATIS Construction Chemicals

Tiranë, Albania

info@matís-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.