

MP-819 BETOPRIME

Primer a base d'acqua ad alta adesione per substrati lisci o non porosi.



IMBALLAGGIO

5kg/20kg



CONSUMO

0.25kg/m²

Descrizione

MP-819 BETOPRIME è un primer di adesione con resine sintetiche e sabbia di quarzo.

Area di utilizzo

-Viene utilizzato su superfici lisce o non assorbenti per aumentare l'adesione dello strato di intonaco o rivestimento.

Preparazione del supporto

La superficie da trattare deve essere asciutta e priva di polvere, grasso, sporco, ecc.

Applicazione

MP-819 BETOPRIME va mescolato e applicato sulla superficie con pennello o rullo.

Consumo

Consuma 0,25 kg/m² a seconda della superficie.

Caratteristiche



Scheda Tecnica (A +23° C E 50% U.R.)

Forma	Impasto
Colore	Rosso scuro
Rilascio di sostanze pericolose	Vedi scheda di sicurezza

MATIS Construction Chemicals

Tiranë, Albania

info@matic-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.