

PG-551 PRIMER GRAFIATO

Astar me bazë uji, i bardhë, akrilik, me rërë kuarci për fasada.



PAKETIMI

5kg/20kg



KONSUMI

0.25kg/m²

Përshkrimi

PG-551 PRIMER GRAFIATO është një astar me bazë uji, i bardhë, akrilik, me rërë kuarci për fasada.

PG-551 PRIMER GRAFIATO siguron një sipërfaqe përfundimtare me ngjyrë uniforme, veçanërisht kur zgjidhet një suva me ngjyrë të errët.

Fusha e Përdorimit

-Përdoret si një primer gati për përdorim para aplikimit të suvave dekorative.

Përgatitja e Sipërfaqes

Sipërfaqja duhet të jetë e pastër nga pluhuri, yndyrat, grimcat, bojërat, etj. Rekomandohet që sipërfaqja të laget para aplikimit.

Aplikimi

PG-551 PRIMER GRAFIATO duhet të përzihet mirë para aplikimit, me lëvizje të ngadalta dhe rrethore për të shmangur futjen e ajrit.

PG-551 PRIMER GRAFIATO aplikohet me furçë ose rrul.

Konsumi

Konsumon 0.25kg/m², në varësi të sipërfaqes.

Karakteristika



Të dhëna teknike (NE +23°C DHE 50% U.R.)

Forma	E lëngshme
Ngjyra	E bardhë
Magazinimi	24 muaj kur ruhet në paketimin origjinal të mbyllur në një vend të thatë.
Densiteti (EN ISO 2811, DIN 53217, ASTM D 1475)	1.65-1.75 g/cm ³
Viskoziteti (RVDV -2T, R7)	5500-6500 cp
pH	≥8
Rezistencë ndaj lagështirës	Thahet pas 24 orësh në kushte normale
Temperatura e aplikimit	(+5°C) - (+35°C)
Forca e ndërveprimit sipërfaqësor (RVDV -2T, R7)	10000-15000 newton/m ²
% (RVDV -2T, R7)	10-70%
Viskoziteti Kinematik (RVDV -2T, R7)	2000-5000 mm ² /s

MATIS Construction Chemicals

Tiranë, Albania

info@matís-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.