

## MF-220 PROFINISH

Ready-to-use, water-based acrylic smoothing compound.



**PACKAGING**  
20kg



**CONSUMPTION**  
2.5-3 m<sup>2</sup>/kg

### Description

MF-220 PROFINISH is a ready-to-use, water-based acrylic smoothing compound designed for interior and exterior substrates. It spreads effortlessly and can be sanded to a perfectly even finish, providing an ideal base for priming and painting.

### Area of Use

-It is perfect for leveling and preparing surfaces such as plaster, concrete, masonry, wood, gypsum board, and cement board.

### Substrate Preparation

The surface must be free of dust, paint, loose material, etc. Priming or preparation with oil is not required prior to application to plaster or concrete. Plasterboards must be primed with MP-809 ACRYPRIME.

### Application

MF-220 PROFINISH is applied with a trowel using a dragging technique in two layers. The second layer is applied once the first has fully dried. After drying, the surface is sanded to achieve a smooth finish before priming and painting

### Consumption

It consumes 2.5-3 m<sup>2</sup>/kg depending on the surface.

### Features



## Technical Data (IN +23 °C AND 50% U.R.)

Form	Paste
Color	White
Density	1.65 ± 0.05 kg/l
Drying time	1-2 hours
Recoat	2-3 hours
Adhesion to gypsum board	0.35 N/mm <sup>2</sup>
Flexural strength	300 N
Release of Dangerous Substances	See SDS

### MATIS Construction Chemicals

Tiranë, Albania

info@matis-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.matis-eu.com](http://www.matis-eu.com), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.