

## MR-840 MATIART R4

Επισκευαστικό κονίαμα υψηλής αντοχής με βάση το τσιμέντο, ενισχυμένο με πολυμερή και Fiber Strength Tech.



### ΣΥΣΚΕΥΑΣΙΑ

25kg



### ΑΝΑΜΙΞΗ

4-5 L/25kg



### ΚΑΤΑΝΑΛΩΣΗ

17 kg/m<sup>2</sup>

### Περιγραφή

Το MR-840 MATIART R4 είναι υψηλής απόδοσης τσιμεντοειδές κονίαμα επισκευής με τεχνολογία Fiber Strength Tech. Σχεδιασμένο για δομικές επισκευές όπου απαιτείται υψηλή αντοχή και ανθεκτικότητα.

### Περιοχή Εφαρμογής

Είναι σχεδιασμένο για βαριές επισκευές σκυροδέματος. Μπορεί να εφαρμοστεί με σπάτουλα ή να ψεκαστεί πνευματικά με τη μέθοδο guniting, καθιστώντας το ιδανικό για χρήση σε δάπεδα, τοίχους και οροφές.

### Προετοιμασία Υποστρώματος

Η επιφάνεια πρέπει να είναι καθαρή από σκόνη, χρώμα, χαλαρά υλικά κ.λπ.

### Εφαρμογή

Το MR-840 MATIART R4 προστίθεται στο νερό υπό συνεχή ανάδευση, έως ότου σχηματιστεί μείγμα της επιθυμητής εργασιμότητας.

### Κατανάλωση

Καταναλώνει 17 kg/m<sup>2</sup>/cm ανάλογα με την επιφάνεια.

### Χαρακτηριστικά



## Τεχνικά Χαρακτηριστικά (Στους +23 °C και

Μορφή	Σκόνη
Χρώμα	Γκρι
Θλιπτική Αντοχή (EN12190)	Κλάση R4
Αντοχή σε Κάμψη	≥ 8,0 N/mm <sup>2</sup>
Θερμική Συμβατότητα (EN 13687-1)	≥ 2 N/mm <sup>2</sup>
Μέτρο Ελαστικότητας	≥ 21 GPa
Αντίδραση στη Φωτιά	A1
Απελευθέρωση Επικίνδυνων Ουσιών	Βλέπε SDS

### **MATIS Construction Chemicals**

Tiranë, Albania

info@matis-eu.com

www.matis-eu.com

T: +355 69 20 94 570

THIS TECHNICAL DATA SHEET SUPERSEDES ALL PREVIOUS EDITIONS RELEVANT TO THIS PRODUCT

2/2

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website [www.matis-eu.com](http://www.matis-eu.com), as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.