MATIS

www.matis-eu.com

PG-551 PRIMER GRAFIATO

Water-based, white, acrylic facade render primer with quartz sand.

PACKAGING
5kg/20kg

CONSUMPTION
0.25kg/m^2

Description
PG-551 PRIMER GRAFIATO is a water-based, white, acrylic facade render primer with quartz sand. PG-551 PRIMER GRAFIATO ensures a uniformly coloured final surface, especially when a dark coloured render has been selected.

Area of Use
-It is used as a ready to use primer before applying the MATIS decorative renders
-It is recommended to use it coloured in the same colour as the render, especially when MT-400 MATIGRAF, GF-22, GS-11, MT-460 SILGRAF, MT-560 SILICONE RENDER and MT-750 SILICONE FAÇADE RENDER renders are to be applied. Suitable for interior and exterior applications.

Substrate Preparation
The surface should be free of dust, grease, loose particles, paints, etc. It is recommended to dampen it before application.

Application
PG-551 PRIMER GRAFIATO should be thoroughly stirred before application, in slow, circular motions to prevent air entrapment.PG-551 PRIMER GRAFIATO is applied by brush or roller.

Consumption
It consumes 0.25kg/m2 depending on the surface.

Features

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.

Technical Data (IN +23°C AND 50% U.R.)

Form	Liquid
Color	White
Storage	24 months when stored in the original sealed packaging in a dry place.
Density (EN ISO 2811, DIN 53217, ASTM D 1475)	1.65-1.75 g/cm³
Viscosity (RVDV -2T, R7)	5500-6500 cp
pH	≥8
Resistance against humidity	Dry after 24 hours in normal condotions
Application Temperature	(+5°C) - (+35°C)
Shear Stress (RVDV -2T, R7)	10000-15000 newton/m²
% (RVDV -2T, R7)	10-70%
Kinematic Viscosity (RVDV -2T, R7)	2000-5000 mm²/s

MATIS Construction Chemicals
Tiranë, Albania
info@matis-eu.com
www.matis-eu.com
T: +355 69 20 94 570

DISCLAIMER: The above technical data, information, recommendations and guidance are based on scientific and technical knowledge, laboratory studies and long experience. However, the above information is considered to be as indicative and should be reviewed in any case in relation to each specific application conditions. Consequently, the suitability of each product in any application must be evaluated after referring to the updated Technical Data Sheet and to the website www.matis-eu.com, as well as after contacting the technical support department, in case of necessity. Our company guarantees the quality of the product itself, whilst in any case the user/applicant is exclusively responsible for any undesirable failures after using the product.