DECLARATION OF PERFORMANCE No.0109

1. Unique identification code of the product-type: MA-405 MATIFLEX
2. Intended use/es: C2TE S1, High-performance, extra-flexible, polymer-modified, cement-based tile adhesive with extended open time and no vertical slip with Fibre Strength Tech.
3. Manufacturer: MATIS CONSTRUCTION CHEMICALS SH.P.K
4.System/s of AVCP: System 3
5.Harmonised standard: EN 12004:2007 + A1:2012
6.Declared performance/s:

Essential characteristics	Performance
Bond Strength, as:	
Initial Tensile Adhesion Strength	⩾ 1 N/mm^2
Durability for:	
Tensile Adhesion Strength after heat ageing	⩾ 1 N/mm2
Tensile Adhesion Strength after water immersion	⩾ 1 N/mm2
Tensile Adhesion Strength after freeze-thaw cycles	⩾ 1 N/mm2
Reaction to Fire	A2
Release of Dangereous Substances	See Safety Data Sheet

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:
Klejdi Guri (legal representative) at Vore, Tirane, on 20/04/2023

MATIS CONSTRUCTION
CHEMICALS SH.P.K
www.matis-eu.com

info@matis-eu.com
+355 68 204 0095

Zona Industriale, Vore,
Tirana, Albania