

MATIS

DECLARATION OF PERFORMANCE No.0110

- 1. Unique identification code of the product-type:** MA-505 TECHNOLAST 10
- 2. Intended use/es:** C2TE, High-performance, flexible, polymer-modified, two components, cement-based tile adhesive with extended open time and no vertical slip with Fibre Strength Tech.
- 3. Manufacturer:** MATIS CONSTRUCTION CHEMICALS SH.P.K
- 4. System/s of AVCP:** System 3
- 5. Harmonised standard:** EN 12004:2007 + A1:2012
- 6. Declared performance/s:**

Essential characteristics	Performance
Bond Strength, as:	
Initial Tensile Adhesion Strength	$\geq 1 \text{ N/mm}^2$
Durability for:	
Tensile Adhesion Strength after heat ageing	$\geq 1 \text{ N/mm}^2$
Tensile Adhesion Strength after water immersion	$\geq 1 \text{ N/mm}^2$
Tensile Adhesion Strength after freeze-thaw cycles	$\geq 1 \text{ N/mm}^2$
Reaction to Fire	A2
Release of Dangerous Substances	See Safety Data Sheet

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by: Klejdi Guri (legal representative) at Vore, Tirane, on 25/05/2024



MATIS CONSTRUCTION
CHEMICALS SH.P.K
www.matis-eu.com



info@matis-eu.com
+355 68 204 0095



Zona Industriale, Vore,
Tirana, Albania