

MATIS

DECLARATION OF PERFORMANCE No.0401

1. Unique identification code of the product-type: MM-420 MATIMOR
2. Intended use/es: Cement-based mortar for masonry construction.
3. Manufacturer: MATIS CONSTRUCTION CHEMICALS SH.P.K
4. System/s of AVCP: System 2+
5. Harmonised standard: EN 998-2:2016
6. Declared performance/s:

Essential characteristics	Performance	Test Method
Compressive strength	M5	EN 1015-11
Bond Strength	0,15 N/mm ² (tabulated)	EN 998-2
Reaction to fire	Class A1	EN 13501-1
Capillary water absorption	0,3 kg/m ² min ^{0,5}	EN 1015-18
Water vapor permeability	μ: 15/35 (tabulated)	EN 1745
Thermal conductivity λ10 dry	0,67 W/mK (tabulated)	EN 1745
Durability (against free/ thaw)	evaluation based on provisions valid in the intended place of use of the mortar	
Release of Dangerous Substances	See Safety Data Sheet	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by: Klejdi Guri (legal representative) at Vore, Tirane, on 17/10/2022



MATIS CONSTRUCTION
CHEMICALS SH.P.K
www.matis-eu.com

info@matis-eu.com
+355 68 204 0095

Zona Industriale, Vore,
Tirana, Albania