DECLARATION OF PERFORMANCE No.0201

1. Unique identification code of the product-type: MT-280 BASECOAT
2. Intended use/es: High-performance base coat render designed for manual or machine application.
3. Manufacturer: MATIS CONSTRUCTION CHEMICALS SH.P.K
4.System/s of AVCP: System 4
5.Harmonised standard: EN 998-1:2016
6.Declared performance/s:

Essential characteristics	Performance	Test Method
Reaction to fire	Class A1	EN 13501-1
Capillary water absorption	$\leqslant 0.2$ kg/m^{2}min$^{0.5}$ W_c2	EN 998-1
Water vapour permeability	$\leqslant 15$	EN 1015-19
Adhesion	$\geqslant 0.10$ N/mm^2 (EPS Failure)	EN 1015-12
Thermal conductivity λ10 dry	0.50 W/mK for P=50%	EN 998-1
Durability	Evaluation based on provisions valid in the intended place of use of the mortar	
Release of Dangereous Substances	See Safety Data Sheet	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:
Klejdi Guri (legal representative) at Vore, Tirane, on 11/01/2026

MATIS CONSTRUCTION CHEMICALS SH.P.K
www.matis-eu.com

info@matis-eu.com
+355 68 204 0095

Zona Industriale, Vore,
Tirana, Albania